



RECHARGEABLE INLINE WATER FILTER

Capable of treating up to 4000 litres of water at pressures up to 6 bar (90 psi).

Your filter should be recharged annually or twice yearly for heavy usage.

IMPORTANT: To prevent the filter splitting during winter, caused by freezing, the carbon bag **MUST** be removed at the end of the season, and when sterilising the system

FITTING INSTRUCTIONS

FOR SEMI-RIGID PIPES USING PUSH FIT CONNECTORS

1. Cut pipe to correct size to accommodate filter and attach the push fit connectors supplied, being sure to push the pipe fully into the connector. **DO NOT USE EXISTING CONNECTORS.**
2. Push connectors fully onto the filter stubs at each end, making sure that the water flow is in the right direction.
3. Check that the screw cap is closed but not over tightened.
4. Flush the filter through for 30 seconds to clear carbon dust from the cartridge (the water will run darkly coloured for a few seconds) and check for leaks.

FOR FLEXIBLE HOSE USING JUBILEE CLIPS

1. Cut pipe to correct size to accommodate filter.
2. Push the two short sleeves over the filter stubs at each end of the filter. Push them firmly down against a hard surface until the sleeve is flush with the end of the stub.
3. Fit jubilee clips over the hose, push the hose over the sleeved stub and tighten into position on the sleeves.
4. Continue as step 4 above.



Filtapac

2 Highcliffe, Wellingore, Lincoln, LN5 0HG

01522 810340 info@filtapac.co.uk

www.filtapac.co.uk